

Fastening power and flexibility.

You have options. Check out the large 3M portfolio of solutions that offer these solutions:

- Clean, smooth “behind the scenes” hold for aesthetic improvements
- Lightweight alternatives to metal fasteners
- Simple to apply, use and maintain
- Variety of strengths to fit your project needs
- Flexibility to fit your designs, even the most constricted areas
- Ability to join dissimilar materials without corrosion and contamination
- Vibration absorption and security — no loosening or failing attachments
- Durable for repeated opening and closings — hundreds of reattachments

Strength Increase

- 3M™ Dual Lock™ Reclosable Fastener **Type 400**
- 3M™ Dual Lock™ Reclosable Fastener **Type 250**
- 3M™ Dual Lock™ Reclosable Fastener **Type 170**
- 3M™ Dual Lock™ Reclosable Fastener **Low Profile**
- 3M™ Hook and Loop Reclosable Fastener **Standard Thickness**
- 3M™ Hook and Loop Reclosable Fastener **Low Profile**

Holding strength increases as you move up from 3M™ Hook and Loop through 3M™ Dual Lock™ Reclosable Fasteners.

3M™ Dual Lock™ Reclosable Fasteners

Stem Density (per sq/in) Combinations

Strongest
250:400

Stronger
250:250
or 170:400

Strong
170:250

Not Recommended
170:170 or 400:400

Interchangeable Strength Combinations



Type 400 Type 250 Type 170 Low Profile

3M™ Hook and Loop Reclosable Fasteners



Hooks on one side, loops on the other for secure, repeated closures.

- Up to 5,000 closures for our standard Hook and Loop
- Low profile options available, as much as 75% thinner than standard product

3M™ Dual Lock™ Reclosable Fasteners

Holding power to replace screws, bolts and rivets.

Durable enough to last through repeated opening and closing. Unique, interlocking mushroom-shaped heads snap shut and stay locked.

- Durable — up to 1,000 openings and closings before losing 50% of original tensile strength
- Helps reduce vibration
- Temperature, moisture and UV resistant
- Strong, pressure-sensitive adhesive bonds on contact
- Mushroom-shaped heads have **5X the tensile strength** of hook-and-loop products

- Best Suggested Product
- Performance Dependent on Selected Attachment Method
- ▲ Primer Recommended

Product	Stem Density (per sq/in)	Adhesive	Color	3M Liner	Engaged Thickness	Temperature Resistance °F (°C)	Substrates					Indoor/Outdoor	Markets									
							Metals (Al & SS)	Glass	Plastics (Acrylic, PC, ABS)	Powder Coated Paints	Low Surface Energy (PP, PE)		Aerospace & Rail	Appliance & Electronics	Design & Construction	Furniture & Upholstery	General Industrial	Marine & Specialty Vehicle	POP, Display & Signage			
SJ3540	250	Rubber	Black	White, 5 mil (0.13mm) Polyolefin	0.23 in (5.7mm)	120 (49)	■	■	■	■	■	Indoor										
SJ3541	400																					
SJ3542	170																					
▶ SJ3550	250	White Acrylic	Black	Clear, 4 mil (0.10mm) Polyolefin	0.23 in (5.7mm)	200 (93)	■	■	■	▲	▲	Indoor/Outdoor	■	■	■	■	■	■	■			
▶ SJ3551	400																					
▶ SJ3552	170																					
SJ3558	250	White Acrylic	Clear*	Clear, 4 mil (0.10mm) Polyolefin	0.23 in (5.7mm)	200 (93)	■	■	■	▲	▲	Indoor/Outdoor	■	■	■	■	■	■	■			
▶ SJ3560	250	Clear Acrylic	Clear	Clear, 4 mil (0.10mm) Polyolefin	0.23 in (5.7mm)	220 (104)	■	■	■	▲	▲	Indoor/Outdoor	■	■	■	■	■	■	■			
SJ3561	400																					
SJ3562	170																					
SJ3550CF	250	Clear Acrylic	Black	Clear, 4 mil (0.10mm) Polyolefin	0.23 in (5.7mm)	220 (104)	■	■	■	▲	▲	Indoor/Outdoor	■	■	■	■	■	■	■			
SJ3551CF	400																					
SJ3552CF	170																					
SJ3870	250	Modified Acrylic	Black	Red, 4.5 mil (0.11mm) Polyolefin	0.24 in (6.1mm)	140 (60)	■	■	■	▲	▲	Indoor/Outdoor	■	■	■	■	■	■	■			
SJ3871	400																					
SJ3872	170																					
SJ3782	250	Low Surface Energy Acrylic	Black	Brown, 83# Polykraft	0.16 in (4.1mm)	120 (49)	■	■	■	■	■	Indoor/Outdoor	■	■	■	■	■	■				
SJ3440	250	None	Black	No Liner	0.15 in (3.86mm)	220 (104)	●	●	●	●	●	Indoor/Outdoor	●	●	●	●	●	●	●			
SJ3441	400																					
SJ3442	170																					
SJ3443	400	Non-woven backing with no adhesive	Black	No Liner	0.28 in (7.1mm)	220 (104)	●	●	●	●	●	Indoor/Outdoor	●	●	●	●	●	●	●			
SJ3444	170																					
SJ3445	250																					
SJ3460	250	None	Clear	No Liner	0.15 in (3.86mm)	220 (104)	●	●	●	●	●	Indoor/Outdoor	●	●	●	●	●	●				
SJ3463	400	Piece Part Circle*	Black	No Liner	0.20 in** (5.1mm)	220 (104)	■	■	■	■	■	Indoor/Outdoor	■	■	■	■	■	■				
SJ3481	400	Rigid Strip*	Black	No Liner	0.20 in** (5.1mm)	220 (104)	●	●	●	●	●	Indoor/Outdoor	●	●	●	●	●	●				
▶ SJ4570	Low Profile/Thin	Low Surface Energy Acrylic	Clear	Brown, 83# Polykraft	0.098 in (2.489mm)	158 (70)	■	■	■	■	■	Indoor/Outdoor	■	■	■	■	■	■				
SJ4575			Black																			
SJ4580			Clear Acrylic				Clear	Red, 4.5 mil (0.11mm) Polyolefin	0.12 in (3.0mm)	200 (93)	■	■	■	▲	▲	Indoor/Outdoor	■	■	■	■	■	

*Clear fastener utilizes a white adhesive giving the product a white appearance **Single thickness; not engaged *No adhesive

▶ [Go-To Product](#)

Note: The technical information and data on these pages should be considered representative or typical only and should not be used for specification purposes.